

LONG RUN ENERGY

A class of Petrol generators designed specially for intensive operations where performance power is demanded by professional users over an extended period of time.



Motorization:

Honda GX270 professional engine. Consumption of 1,3 liters per hour, manual start, tank of 25 liters. This engine has an autonomy of 20 hours at 75% of load.

AVR

AVR:

Automatic Voltage Regulation which allow to remove the risk to damage high technology devices.



Socket:

This single phase generator has two SCHUKO sockets protected by a circuit breaker.

MODEL	X 5000	
SINGLE PHASE		
(POWER LTP)	4,5/4,1	kW/kVA
(POWER COP)	3,7/3,3	kW/kVA
POWER SPECIFICATIONS		
VOLTAGE	230	Volt
FREQUENCY	50	Hz
POWER FACTOR	0,9	cos
ENGINE		
BRAND	Honda	
MODEL	GX270	
FUEL	Petrol	
DISPLACEMENT	270	CC
SPEED	3000	rpm
CYLINDER	1 inclined	
COOLING SYSTEM	Air	
STARTING SYSTEM	Electric or Recoil	
CONSUMPTION		
CONSUMPTION at 75% of load	1,3	L/H
FUEL TANK CAPACITY	25	L
RUNNING TIME at 75% of load	20	H
NOISE EMISSION		
GUARRANTEED SOUND LEVEL LWA	-	dB(a)
NOISE PRESSURE LEVEL at 7 mt	-	dB(a)
DIMENSIONS AND WEIGHT		
LENGTH	811	mm
WIDTH	557	mm
HEIGHT	543	mm
WEIGHT (dry)	73 or 66 (Electric or Recoil)	
SOCKET TYPE		
2 X SCHUKO 230V		
ALTERNATOR AND SOCKET PROTECTION		
ELECTRIC PROTECTION	IP 23	
SOCKET PROTECTION	IP 54	
OIL GUARD SYSTEM	YES	
THERMAL PROTECTION	YES	



ACCESSORIES

STANDARD TRANSPORTATION KIT
TRANSPORTATION KIT WITH FOLDED HANDLES
MANUAL TRANSFER SWITCH 40A 230 V
COVER (760 x 540 x 550 mm)