

## LONG RUN ENERGY

A class of Petrol generators designed specially for intensive operations where performance power is demanded by professional users over an extended period of time.



### Motorization:

Honda GX160 professional engine. Consumption of 0,8 liters per hour, manual start, tank of 16 liters. This engine has an autonomy of 21 hours at 75% of load.

# AVR

### AVR:

Automatic Voltage Regulation which allow to remove the risk to damage high technology devices.



### Socket:

This single phase generator has two SCHUKO sockets protected by a circuit breaker.

MODEL		X 3000
SINGLE PHASE		
(POWER LTP)	2,6/2,3	kW/kVA
(POWER COP)	2,0/1,8	kW/kVA
POWER SPECIFICATIONS		
VOLTAGE	230	Volt
FREQUENCY	50	Hz
POWER FACTOR	0,9	cos
ENGINE		
BRAND	Honda	
MODEL	GX160H1	
FUEL	Petrol	
DISPLACEMENT	163	CC
SPEED	3000	rpm
CYLINDER	1 inclined	
COOLING SYSTEM	Air	
STARTING SYSTEM	Recoil	
CONSUMPTION		
CONSUMPTION at 75% of load	0,8	L/H
FUEL TANK CAPACITY	16	L
RUNNING TIME at 75% of load	21	H
NOISE EMISSION		
GUARRANTEED SOUND LEVEL LWA	-	dB(a)
NOISE PRESSURE LEVEL at 7 mt	-	dB(a)
DIMENSIONS AND WEIGHT		
LENGTH	675	mm
WIDTH	454	mm
HEIGHT	508	mm
WEIGHT (dry)	47	Kg
SOCKET TYPE		
2 X SCHUKO 230V		
ALTERNATOR AND SOCKET PROTECTION		
ELECTRIC PROTECTION	IP 23	
SOCKET PROTECTION	IP 54	
OIL GUARD SYSTEM	YES	
THERMAL PROTECTION	YES	



#### ACCESSORIES

STANDARD TRANSPORTATION KIT
TRANSPORTATION KIT WITH FOLDED HANDLES
MANUAL TRANSFER SWITCH 40A 230 V
COVER (760 x 540 x 550 mm)